

ROUND

Photocell for exterior, till 30mt



The photocell ROUND is the result of several years of research in the field of automatic openings of doors and gates and is particularly suitable for the control of transit and for protection. It is constructed in compliance of the norms with two independent relays. It is fed with a voltage range between 10 and 30Vac/Vcc. Its simple and rational design, always with the high productive quality of PROGET, makes this photocell the best on the market.



ROUND

Main characteristics

- **The possibility of being fixed directly on the wall without using any chase boxes. If already present any box, it can be easily fitted to the different bearings.**
- **Its low profile without any roughness and the strength of the materials used allow a high protection against collisions**
- **Its high protection against sunbeams neon, glow lamps and various other light sources**
- **Its (just like hermetic) against dust and small insects nests**
- **Its low profile without any roughness and the strength of the materials used allow a high protection against collisions. Easy installation: thanks to its round shape it is only necessary to fix transmitter and receiver to two levels, opposite surfaces without any problem of alignment and adjustment for a useful transit light of 10mt, for external use (30mt for internal use) even in case of a shift up to 5 degrees**

Technical characteristics

Feeding	12/24Vac/Vdc
Contacts capacity	2A a 24Vdc
Absorption in transmission	60mA a 24Vdc
Working temperature	-30°C + 55°C
Luminous range in exterior	10m
Luminous range in interior	30m
Protection	Ip555

